



SECTION

THIS DRAWING IS THE PROPERTY OF THE BILCO COMPANY AND INCORPORATES INFORMATION WHICH IS PROPRIETARY. PUBLICATION AND/OR PUBLIC DISTRIBUTION IN WHOLE OR IN PART IS EXPRESSLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF THE BILCO COMPANY. THE INFORMATION CONTAINED HEREIN REMAINS THE PROPERTY OF THE BILCO COMPANY. ALL RIGHTS RESERVED.

SPECIFICATIONS

1. CURB W/INTEGRAL CAPFLASHING – 3mm ALUMINIUM (CORNERS FULLY WELDED)
2. COVER – 3mm ALUMINIUM
3. COVER LINER – 1mm ALUMINIUM
4. 50MM POLYISOCYANURATE CURB INSULATION
5. 50MM POLYISOCYANURATE COVER INSULATION
6. EPDM GASKET (ALL AROUND COVER)
7. PINTLE HINGE – STAINLESS STEEL TYPE 316
8. Bilclip® FLASHING SYSTEM
9. ACTUATOR WITH CARRIAGE – 24VDC (SEE NOTE 1)
10. JUNCTION BOX
11. WIND DEFLECTOR – 4mm ALUMINIUM

SHOP FINISH

ALUMINIUM: MILL FINISH
 HARDWARE: CORROSION RESISTANT
 (UNLESS OTHERWISE SPECIFIED)

NOTES:

1. THE TRAVEL OF THE ACTUATOR WILL PASS BELOW THE BASE MOUNTING FLANGE POSITION. ENSURE THERE ARE NO OBSTRUCTIONS BELOW.
2. THIS PRODUCT IS DESIGNED TO BE INSTALLED ON A FLAT ROOF.
3. FULL SPECIFICATIONS ARE AVAILABLE ON WEBSITE: www.bilco.com

CUSTOMER

P.O. NO.

JOB

SALES REP.

Bilco® Manufacturers of Doors for Special Services
 THE BILCO COMPANY
 New Haven, Connecticut 06505

**SINGLE LEAF SMOKE VENT
 TYPE ESW-50REM**

QTY	TYPE	SIZE WIDTH x LENGTH
<input type="checkbox"/>	ESW-50REM	1260mm x 1260mm HINGE SIDE

Web Site: www.bilco.com