



SECTION

**SPECIFICATIONS**

1. CURB W/ INTEGRAL CAPFLASHING – 3mm ALUMINUM (CORNERS FULLY WELDED)
2. COVER – 3mm ALUMINUM
3. COVER LINER – 1mm ALUMINUM
4. 50mm POLYISOCYANURATE CURB INSULATION
5. 50mm POLYISOCYANURATE COVER INSULATION
6. EPDM GASKET (ALL AROUND COVER)
7. PINTLE HINGE – STAINLESS STEEL TYPE 316
8. Bilclip® FLASHING SYSTEM
9. ACTUATOR – 24VDC
10. JUNCTION BOX
11. FIXED CENTER DRAIN
12. WIND DEFLECTOR – 4mm ALUMINUM

**SHOP FINISH**

ALUMINUM: MILL FINISH  
 HARDWARE: CORROSION RESISTANT  
 (UNLESS OTHERWISE SPECIFIED)

**NOTES:**

1. THIS PRODUCT MAY BE INSTALLED ON EITHER A FLAT OR SLOPING ROOF. WHEN INSTALLED ON A SLOPE, THE HINGE SIDE MUST RUN PARALLEL WITH THE SLOPE. IF SLOPE EXCEEDS 30°, ADVISE FACTORY FOR MODIFICATION.
2. FULL SPECIFICATIONS ARE AVAILABLE ON WEBSITE: [www.bilco.com](http://www.bilco.com)

CUSTOMER

P.O. NO.

JOB

SALES REP.

**Bilco**® Manufacturers of Doors for Special Services  
 THE BILCO COMPANY  
 New Haven, Connecticut 06505

**DOUBLE LEAF SMOKE VENT  
 TYPE UDF-50REM**

QTY	TYPE	SIZE WIDTH x LENGTH HINGE SIDE
	UDF-50REM	1500mm x 1620mm

Web Site: [www.bilco.com](http://www.bilco.com)

THIS DRAWING IS THE PROPERTY OF THE BILCO COMPANY AND INCORPORATES INFORMATION WHICH IS PROPRIETARY. PUBLICATION AND/OR PUBLIC DISTRIBUTION IN WHOLE OR IN PART IS EXPRESSLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF THE BILCO COMPANY. THE INFORMATION CONTAINED HEREIN REMAINS THE PROPERTY OF THE BILCO COMPANY. ALL RIGHTS RESERVED.